PN - JP62007019 A 1987 J114

PD - 1987-01-14

PR - JP19850145780 19850704

OPD - 1985-07-04

TI - DISPLAY DEVICE

IN - KUCHITSU TAKUYO

PA - FUYO SANGYO KK

IC - G02B27/08; G09F9/30

CT - JP57190519B B []; US3501217 A []

@ PAJ / JPO

PN - JP62007019 A 19870114

PĎ - 1987-01-14

AP - JP19850145780 19850704

IN - KUCHITSU TAKUYO

PA - FUYO SANGYO:KK

TI - DISPLAY DEVICE

- PURPOSE:To express an extremely complex pattern by forming colored transparent small chips or the like, forming many virtual images through a cylindrical mirror surface body obtained by combining several reflecting mirror surfaces and expanding the images to project them on a screen.

- CONSTITUTION: Subjects such as colored transparent sheet-like small chips are inserted into a space part 7 of a moving body 2 so as to be freely rotated. A light source 3 and the cylindrical mirror surface body 1 obtained by combining three reflecting mirror surfaces 1a are arranged on both the sides of the moving body 2. When the moving body 2 is rotated and light is irradiated from the light source 3, many virtual images of the subjects 6 are formed by the reflection of light in the cylindrical body 1 like a kaleidoscope and projected on the screen 5 through an expanding lens 4. Consequently, extremely complex patterns can be automatically and continuously displayed and can be used for various purposes.

- G02B27/08 ;G09F9/30

none